

Monomeric transparent matt laminate featuring a permanent acrylic adhesive. This material has been specifically designed for protecting digital prints.

IP 2820-200

Monomeric film featuring specific polymeric, non-migrating plasticizers and UV stabilizers, which ensure maximum light fastness and good outdoor durability. IP 2820-200 is intended for many flat applications, both interior and exterior, such as markings & decorations, window and vehicle graphics, with its B1 fire rating further increases the application opportunities. This laminate can be used on IP 2511 - IP 2514, IP 2524 - IP 2527 and IP 2528 - IP 2531, as well as on many other speciality materials such as IP 2901FR, IP 2903, IP 2905, IP 2906, IP 2909 and IP 2910.

Specifications	
DESCRIPTION	Monomeric laminate
COLOUR	Transparent matt
FACE FILM THICKNESS	80 μ
WEIGHT	N/A
ADHESIVE	Acrylic permanent
ADHESIVE STRENGTH	16N / 25mm (Finat TM 1/24h)
RELEASE PAPER	PE-coated silicone paper, 140g / m ²
TEMPERATURE RANGE	-40°C to +80°C
DURABILITY (UNPRINTED)	Up to 3 years
FLAME RETARDANCY	B1
SHELF LIFE	2 years, 20°C / 50% humidity
RECOMMENDATION	For optimum quality, please ensure that the media feed adjustment has been completed for this material

© December 2010 Spandex Group. Technical specifications subject to change without prior notice. All trademarks mentioned are property of their respective owners. Output may vary depending on the type of print data/file, application, media, environmental conditions, print speed, or other variables.